

This information was generated by the HP KEYMARK database on 25 Feb 2023

	DE DIETRICH Alezio S V200 R32 6/8 MR	Reg. No.	21HK0010/00
Certificate Holder			
	BDR Thermea FR (DE DIETRICH)		
	57 rue de la Gare		67580
	Mertzwiller		France
Certification Body	Kiwa Nederland B.V.		
Subtype title	DE DIETRICH Alezio S V200 R32 6/8 MR		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	1.2 kg		
Certification Date	12.11.2021		
Testing basis	European KEYMARK Scheme for Heat Pumps (v9)		

Model: AWHPR 6 MR + MIV-S/E 4-8 V200 R32

Configure model	
Model name	AWHPR 6 MR + MIV-S/E 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	6.40 kW	5.70 kW
El input	1.28 kW	1.97 kW
COP	5.00	2.90

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.30 kW	1.43 kW
Cooling capacity	6.50	7.00
EER	2.83	4.88

EN 14825

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
P _{designc}	6.50 kW	7.00 kW
SEER	3.95	5.99
P _{dc Tj = 35°C}	6.50 kW	7.00 kW
EER T _j = 35°C	2.83	4.88
P _{dc Tj = 30°C}	4.90 kW	5.39 kW
EER T _j = 30°C	3.99	6.65
C _{dc Tj = 30 °C}	0.990	0.980
P _{dc Tj = 25°C}	3.10 kW	3.32 kW
EER T _j = 25°C	4.55	4.93
C _{dc Tj = 25 °C}	0.980	0.980
P _{dc Tj = 20°C}	1.37 kW	1.78 kW
EER T _j = 20°C	3.96	9.48
C _{dc Tj = 20 °C}	0.960	0.930
P _{off}	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Q _{ce}	987 kWh	701 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	31 dB(A)	31 dB(A)
Sound power level outdoor	57 dB(A)	57 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	177 %	132 %
Prated	6.50 kW	6.00 kW
SCOP	4.50	3.37
Tbiv	-10 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.90 kW	5.50 kW
COP Tj = -7°C	3.16	2.22
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.50 kW	3.40 kW
COP Tj = +2°C	4.48	3.37
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.30 kW	2.10 kW
COP Tj = +7°C	5.61	4.07
Cdh Tj = +7 °C	0.960	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.50 kW	2.50 kW
COP Tj = 12°C	6.92	6.58
Cdh Tj = +12 °C	0.960	0.970
Pdh Tj = Tbiv	6.50 kW	5.50 kW
COP Tj = Tbiv	2.68	2.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.50 kW	5.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.68	1.82
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.70 kW
Annual energy consumption Qhe	2986 kWh	3679 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	128 %
COP	3.07
Heating up time	01:32 h:min
Standby power input	28.3 W
Reference hot water temperature	54.1 °C
Mixed water at 40°C	255 l

Model: AWHPR 6 MR + MIV-S/H 4-8 V200 R32

Configure model	
Model name	AWHPR 6 MR + MIV-S/H 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	6.40 kW	5.70 kW
El input	1.28 kW	1.97 kW
COP	5.00	2.90

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.30 kW	1.43 kW
Cooling capacity	6.50	7.00
EER	2.83	4.88

EN 14825

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
P _{designc}	6.50 kW	7.00 kW
SEER	3.95	5.99
P _{dc Tj = 35°C}	6.50 kW	7.00 kW
EER Tj = 35°C	2.83	4.88
P _{dc Tj = 30°C}	4.90 kW	5.39 kW
EER Tj = 30°C	3.99	6.65
C _{dc Tj = 30 °C}	0.990	0.980
P _{dc Tj = 25°C}	3.10 kW	3.32 kW
EER Tj = 25°C	4.55	4.93
C _{dc Tj = 25 °C}	0.980	0.980
P _{dc Tj = 20°C}	1.37 kW	1.78 kW
EER Tj = 20°C	3.96	9.48
C _{dc Tj = 20 °C}	0.960	0.930
P _{off}	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Q _{ce}	987 kWh	701 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	31 dB(A)	31 dB(A)
Sound power level outdoor	57 dB(A)	57 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	177 %	132 %
Prated	6.50 kW	6.00 kW
SCOP	4.50	3.37
Tbiv	-10 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.90 kW	5.50 kW
COP Tj = -7°C	3.16	2.22
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.50 kW	3.40 kW
COP Tj = +2°C	4.48	3.37
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.30 kW	2.10 kW
COP Tj = +7°C	5.61	4.07
Cdh Tj = +7 °C	0.960	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.50 kW	2.50 kW
COP Tj = 12°C	6.92	6.58
Cdh Tj = +12 °C	0.960	0.970
Pdh Tj = Tbiv	6.50 kW	5.50 kW
COP Tj = Tbiv	2.68	2.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.50 kW	5.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.68	1.82
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.70 kW
Annual energy consumption Qhe	2986 kWh	3679 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	128 %
COP	3.07
Heating up time	01:32 h:min
Standby power input	28.3 W
Reference hot water temperature	54.1 °C
Mixed water at 40°C	255 l

Model: AWHPR 6 MR + MIV-S/E 4-8 V200 R32

Configure model	
Model name	AWHPR 6 MR + MIV-S/E 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	6.40 kW	5.70 kW
El input	1.28 kW	1.97 kW
COP	5.00	2.90

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.30 kW	1.43 kW
Cooling capacity	6.50	7.00
EER	2.83	4.88

EN 14825		

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
P _{designc}	6.50 kW	7.00 kW
SEER	3.95	5.99
P _{dc Tj = 35°C}	6.50 kW	7.00 kW
EER Tj = 35°C	2.83	4.88
P _{dc Tj = 30°C}	4.90 kW	5.39 kW
EER Tj = 30°C	3.99	6.65
C _{dc Tj = 30 °C}	0.990	0.980
P _{dc Tj = 25°C}	3.10 kW	3.32 kW
EER Tj = 25°C	4.55	4.93
C _{dc Tj = 25 °C}	0.980	0.980
P _{dc Tj = 20°C}	1.37 kW	1.78 kW
EER Tj = 20°C	3.96	9.48
C _{dc Tj = 20 °C}	0.960	0.930
P _{off}	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Q _{ce}	987 kWh	701 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	31 dB(A)	31 dB(A)
Sound power level outdoor	57 dB(A)	57 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	177 %	132 %
Prated	6.50 kW	6.00 kW
SCOP	4.50	3.37
Tbiv	-10 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.90 kW	5.50 kW
COP Tj = -7°C	3.16	2.22
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.50 kW	3.40 kW
COP Tj = +2°C	4.48	3.37
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.30 kW	2.10 kW
COP Tj = +7°C	5.61	4.07
Cdh Tj = +7 °C	0.960	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.50 kW	2.50 kW
COP Tj = 12°C	6.92	6.58
Cdh Tj = +12 °C	0.960	0.970
Pdh Tj = Tbiv	6.50 kW	5.50 kW
COP Tj = Tbiv	2.68	2.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.50 kW	5.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.68	1.82
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.70 kW
Annual energy consumption Qhe	2986 kWh	3679 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	M
Efficiency η_{DHW}	122 %
COP	2.88
Heating up time	01:32 h:min
Standby power input	20.4 W
Reference hot water temperature	54.2 °C
Mixed water at 40°C	261 l

Model: AWHPR 6 MR + MIV-S/H 4-8 V200 R32

Configure model	
Model name	AWHPR 6 MR + MIV-S/H 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	6.40 kW	5.70 kW
El input	1.28 kW	1.97 kW
COP	5.00	2.90

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.30 kW	1.43 kW
Cooling capacity	6.50	7.00
EER	2.83	4.88

EN 14825

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
P _{designc}	6.50 kW	7.00 kW
SEER	3.95	5.99
P _{dc Tj = 35°C}	6.50 kW	7.00 kW
EER Tj = 35°C	2.83	4.88
P _{dc Tj = 30°C}	4.90 kW	5.39 kW
EER Tj = 30°C	3.99	6.65
C _{dc Tj = 30 °C}	0.990	0.980
P _{dc Tj = 25°C}	3.10 kW	3.32 kW
EER Tj = 25°C	4.55	4.93
C _{dc Tj = 25 °C}	0.980	0.980
P _{dc Tj = 20°C}	1.37 kW	1.78 kW
EER Tj = 20°C	3.96	9.48
C _{dc Tj = 20 °C}	0.960	0.930
P _{off}	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Q _{ce}	987 kWh	701 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	31 dB(A)	31 dB(A)
Sound power level outdoor	57 dB(A)	57 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	177 %	132 %
Prated	6.50 kW	6.00 kW
SCOP	4.50	3.37
Tbiv	-10 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.90 kW	5.50 kW
COP Tj = -7°C	3.16	2.22
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.50 kW	3.40 kW
COP Tj = +2°C	4.48	3.37
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.30 kW	2.10 kW
COP Tj = +7°C	5.61	4.07
Cdh Tj = +7 °C	0.960	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.50 kW	2.50 kW
COP Tj = 12°C	6.92	6.58
Cdh Tj = +12 °C	0.960	0.970
Pdh Tj = Tbiv	6.50 kW	5.50 kW
COP Tj = Tbiv	2.68	2.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.50 kW	5.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.68	1.82
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.70 kW
Annual energy consumption Qhe	2986 kWh	3679 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	M
Efficiency η_{DHW}	122 %
COP	2.88
Heating up time	01:32 h:min
Standby power input	20.4 W
Reference hot water temperature	54.2 °C
Mixed water at 40°C	261 l

Model: AWHPR 8 MR + MIV-S/E 4-8 V200 R32

Configure model	
Model name	AWHPR 8 MR + MIV-S/E 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	7.67 kW	8.18 kW
El input	1.62 kW	2.88 kW
COP	4.73	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.33 kW	1.45 kW
Cooling capacity	6.50	7.10
EER	2.79	4.88

EN 14825

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
P _{designc}	6.50 kW	7.10 kW
SEER	4.32	5.82
P _{dc Tj = 35°C}	6.50 kW	7.10 kW
EER Tj = 35°C	2.79	4.88
P _{dc Tj = 30°C}	4.97 kW	5.65 kW
EER Tj = 30°C	3.96	6.71
C _{dc Tj = 30 °C}	0.990	0.990
P _{dc Tj = 25°C}	3.35 kW	3.18 kW
EER Tj = 25°C	4.74	5.26
C _{dc Tj = 25 °C}	0.980	0.980
P _{dc Tj = 20°C}	1.55 kW	1.67 kW
EER Tj = 20°C	5.50	7.40
C _{dc Tj = 20 °C}	0.950	0.930
P _{off}	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Q _{ce}	904 kWh	732 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	32 dB(A)	32 dB(A)
Sound power level outdoor	59 dB(A)	59 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	176 %	125 %
Prated	7.00 kW	7.00 kW
SCOP	4.48	3.21
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	6.06 kW	6.19 kW
COP Tj = -7°C	2.97	1.95
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	4.12 kW	3.79 kW
COP Tj = +2°C	4.46	3.24
Cdh Tj = +2 °C	0.980	0.990
Pdh Tj = +7°C	2.78 kW	2.49 kW
COP Tj = +7°C	5.70	4.10
Cdh Tj = +7 °C	0.970	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.67 kW	2.55 kW
COP Tj = 12°C	7.80	6.10
Cdh Tj = +12 °C	0.960	0.960
Pdh Tj = Tbiv	6.06 kW	6.19 kW
COP Tj = Tbiv	2.97	1.95
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.64 kW	4.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.58	1.66
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.36 kW	2.10 kW
Annual energy consumption Qhe	3225 kWh	4504 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	125 %
COP	2.99
Heating up time	01:41 h:min
Standby power input	30.0 W
Reference hot water temperature	54.9 °C
Mixed water at 40°C	264 l

Model: AWHPR 8 MR + MIV-S/H 4-8 V200 R32

Configure model	
Model name	AWHPR 8 MR + MIV-S/H 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	7.67 kW	8.18 kW
El input	1.62 kW	2.88 kW
COP	4.73	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.33 kW	1.45 kW
Cooling capacity	6.50	7.10
EER	2.79	4.88

EN 14825		

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
P _{designc}	6.50 kW	7.10 kW
SEER	4.32	5.82
P _{dc Tj = 35°C}	6.50 kW	7.10 kW
EER Tj = 35°C	2.79	4.88
P _{dc Tj = 30°C}	4.97 kW	5.65 kW
EER Tj = 30°C	3.96	6.71
C _{dc Tj = 30 °C}	0.990	0.990
P _{dc Tj = 25°C}	3.35 kW	3.18 kW
EER Tj = 25°C	4.74	5.26
C _{dc Tj = 25 °C}	0.980	0.980
P _{dc Tj = 20°C}	1.55 kW	1.67 kW
EER Tj = 20°C	5.50	7.40
C _{dc Tj = 20 °C}	0.950	0.930
P _{off}	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Q _{ce}	904 kWh	732 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	32 dB(A)	32 dB(A)
Sound power level outdoor	59 dB(A)	59 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	176 %	125 %
Prated	7.00 kW	7.00 kW
SCOP	4.48	3.21
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	6.06 kW	6.19 kW
COP Tj = -7°C	2.97	1.95
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	4.12 kW	3.79 kW
COP Tj = +2°C	4.46	3.24
Cdh Tj = +2 °C	0.980	0.990
Pdh Tj = +7°C	2.78 kW	2.49 kW
COP Tj = +7°C	5.70	4.10
Cdh Tj = +7 °C	0.970	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.67 kW	2.55 kW
COP Tj = 12°C	7.80	6.10
Cdh Tj = +12 °C	0.960	0.960
Pdh Tj = Tbiv	6.06 kW	6.19 kW
COP Tj = Tbiv	2.97	1.95
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.64 kW	4.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.58	1.66
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.36 kW	2.10 kW
Annual energy consumption Qhe	3225 kWh	4504 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	125 %
COP	2.99
Heating up time	01:41 h:min
Standby power input	30.0 W
Reference hot water temperature	54.9 °C
Mixed water at 40°C	264 l

Model: AWHPR 8 MR + MIV-S/E 4-8 V200 R32

Configure model	
Model name	AWHPR 8 MR + MIV-S/E 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	7.67 kW	8.18 kW
El input	1.62 kW	2.88 kW
COP	4.73	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.33 kW	1.45 kW
Cooling capacity	6.50	7.10
EER	2.79	4.88

EN 14825

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
Pdesignc	6.50 kW	7.10 kW
SEER	4.32	5.82
Pdc Tj = 35°C	6.50 kW	7.10 kW
EER Tj = 35°C	2.79	4.88
Pdc Tj = 30°C	4.97 kW	5.65 kW
EER Tj = 30°C	3.96	6.71
Cdc Tj = 30 °C	0.990	0.990
Pdc Tj = 25°C	3.35 kW	3.18 kW
EER Tj = 25°C	4.74	5.26
Cdc Tj = 25 °C	0.980	0.980
Pdc Tj = 20°C	1.55 kW	1.67 kW
EER Tj = 20°C	5.50	7.40
Cdc Tj = 20 °C	0.950	0.930
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Qce	904 kWh	732 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	32 dB(A)	32 dB(A)
Sound power level outdoor	59 dB(A)	59 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	176 %	125 %
Prated	7.00 kW	7.00 kW
SCOP	4.48	3.21
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	6.06 kW	6.19 kW
COP Tj = -7°C	2.97	1.95
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	4.12 kW	3.79 kW
COP Tj = +2°C	4.46	3.24
Cdh Tj = +2 °C	0.980	0.990
Pdh Tj = +7°C	2.78 kW	2.49 kW
COP Tj = +7°C	5.70	4.10
Cdh Tj = +7 °C	0.970	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.67 kW	2.55 kW
COP Tj = 12°C	7.80	6.10
Cdh Tj = +12 °C	0.960	0.960
Pdh Tj = Tbiv	6.06 kW	6.19 kW
COP Tj = Tbiv	2.97	1.95
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.64 kW	4.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.58	1.66
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.36 kW	2.10 kW
Annual energy consumption Qhe	3225 kWh	4504 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	M
Efficiency η_{DHW}	121 %
COP	2.84
Heating up time	01:41 h:min
Standby power input	22.0 W
Reference hot water temperature	55.2 °C
Mixed water at 40°C	272 l

Model: AWHPR 8 MR + MIV-S/H 4-8 V200 R32

Configure model	
Model name	AWHPR 8 MR + MIV-S/H 4-8 V200 R32
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C and +18°C/+23°C

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	7.67 kW	8.18 kW
El input	1.62 kW	2.88 kW
COP	4.73	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Cooling

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 14511-2		
	+7°C/+12°C	+18°C/+23°C
El input	2.33 kW	1.45 kW
Cooling capacity	6.50	7.10
EER	2.79	4.88

EN 14825

This information was generated by the HP KEYMARK database on 25 Feb 2023

	+7°C/+12°C	+18°C/+23°C
Pdesignc	6.50 kW	7.10 kW
SEER	4.32	5.82
Pdc Tj = 35°C	6.50 kW	7.10 kW
EER Tj = 35°C	2.79	4.88
Pdc Tj = 30°C	4.97 kW	5.65 kW
EER Tj = 30°C	3.96	6.71
Cdc Tj = 30 °C	0.990	0.990
Pdc Tj = 25°C	3.35 kW	3.18 kW
EER Tj = 25°C	4.74	5.26
Cdc Tj = 25 °C	0.980	0.980
Pdc Tj = 20°C	1.55 kW	1.67 kW
EER Tj = 20°C	5.50	7.40
Cdc Tj = 20 °C	0.950	0.930
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Annual energy consumption Qce	904 kWh	732 kWh

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	32 dB(A)	32 dB(A)
Sound power level outdoor	59 dB(A)	59 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	176 %	125 %
Prated	7.00 kW	7.00 kW
SCOP	4.48	3.21
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	6.06 kW	6.19 kW
COP Tj = -7°C	2.97	1.95
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	4.12 kW	3.79 kW
COP Tj = +2°C	4.46	3.24
Cdh Tj = +2 °C	0.980	0.990
Pdh Tj = +7°C	2.78 kW	2.49 kW
COP Tj = +7°C	5.70	4.10
Cdh Tj = +7 °C	0.970	0.970

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	2.67 kW	2.55 kW
COP Tj = 12°C	7.80	6.10
Cdh Tj = +12 °C	0.960	0.960
Pdh Tj = Tbiv	6.06 kW	6.19 kW
COP Tj = Tbiv	2.97	1.95
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.64 kW	4.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.58	1.66
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.36 kW	2.10 kW
Annual energy consumption Qhe	3225 kWh	4504 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	M
Efficiency η_{DHW}	121 %
COP	2.84
Heating up time	01:41 h:min
Standby power input	22.0 W
Reference hot water temperature	55.2 °C
Mixed water at 40°C	272 l